



DATA SHEET

MULTILAN ACRYLIC DECORATIVE PAINT

Product description:

Ecological paint produced on the basis of the latest generation ingredients. Specially selected ingredients make our paint has a raised one abrasion resistance.

Multilan does not contain any solvents that could have a negative impact on the environment around us, thanks to which we can recommend our product for wide use without any worries. Painted surfaces are characterized by an imitation of granite that is pleasing to the eye, and increased opacity affects economic use of paint.

Application:

Multilan acrylic decorative paint is designed for decorative painting walls and ceilings indoors. Optically masks soil imperfections, convenient in application, ensures correct microventilation of the surface, e.g. kitchen and bathroom.

The paint can be used outdoors for decoration, e.g. facades, elevation columns, window sills, wood, concrete, ceramics and plastics.

Main features:

- ✓ visual imitation of stone
- ✓ 3D effect
- ✓ allows proper microventilation of the surface
- ✓ optically masks surface imperfections
- ✓ easy application with
- ✓ maximum elimination of streaks
- ✓ prevents dust accumulation
- ✓ very efficient, no paint remains in the container

Number of layers:	1
Drying time (room temp.):	5 - 6 hours
Application method:	HVLP spray gun, nozzle >2,5 mm
Paint performance :	4 m²/kg - 20 m²/kg



HOW TO USE

1. Surface preparation

- Remove the remains of the glue paints thoroughly
- the substrate must be free from stains and efflorescences of biological and chemical origin (in the case of the presence of such spots and efflorescence should be used special materials intended for them liquidation)
- surface to be painted should be clean, dry, dust free and without cracks
- fresh plasters and substrates that strongly absorb water (plasterboard, gypsum plaster, substrates never unpainted) prime with a **silicate primer**
- surfaces painted with emulsion paints degrease
- substrates that are highly absorbent, loosely bound, falling apart and chalking (that means leaving traces of dust after rubbing with your hand), paint with **wall primer**
- the best final effect will be provided if good surface preparation will be done first

2. Painting

- fresh plasters should be painted 3-4 weeks after it has been applied
- apply only with HVLP spray gun (low air pressure, a lot of paint)
 - unified application speed
 - repeatability of the pattern
 - low pressure of gun prevents scattering of colored spots
 - uniform layer thickness
- spray gun stream must be 90° to the painted surface, „S” letter move
- good weather while painting (no fog, no rain, no snow)
- **only one layer of paint, do not mix, do not thin**

3. Additional information

- painting temperature +5° C do +30° C
- clean tools with water after work is finished
- during painting and after it is finished, rooms should be ventilated till characteristic smell is gone

Expiration date: 24 months after production date if in original not opened pack in cool room, but protected against frost

If opened, paint should be used in 30 days

Packing: 1kg, 2 kg, 5 kg